

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01

PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

00623-0001

**1. Identification of the substance/preparation and of the company/undertaking****1.1 Identification of the substance or preparation**

PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

Further product name / Art.-No.:

PFC-10 ml (SKU No. 2205010); PFC-8 (SKU No. 2205020); PFC-32 (SKU No. 2205030); PFCG-1 (SKU No. 2205250); PFCG-32 (SKU No. 2205200); PIV-8FT (SKU No. 2205110)

Use of the substance/preparation

Adhesive

1.2 Company/undertaking identification

PREMA GmbH

Aspertsham 40

D-94081 Fürstenzell

Telephone : (++)49 8502 91 76 39

Inquiry office :

Emergency telephone :++49 (0) 6132 / 84463 GBK Gefahrgut Buero GmbH, Ingelheim

2. Composition/information on ingredients**Chemical characterization** (preparation)

Preparation in organic solvents

Hazardous components

EC-No.	CAS-No.	Chemical name	Quantity	Classification
205-563-8	142-82-5	n-Heptane	< 75 %	F, Xn, Xi, N R11-65-38-67-50-53
200-662-2	67-64-1	Acetone	< 20 %	F, Xi R11-36-66-67

Full text of each relevant R phrase can be found in heading 16.

3. Hazards identification**Classification**

Symbols : Highly flammable, Irritant, Dangerous for the environment

R-phrases :

Highly flammable.

Irritating to skin.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01



PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

00623-0001

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arriving from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

7. Handling and storage



7.1 Handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2 Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI) :

3 A

8. Exposure controls/personal protection

8.1 Exposure limit values

Exposure limits (EH40)

CAS No.	Substance	ml/m ³	mg/m ³	F/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
	Acetone	1500	3620		STEL (15 min)	WEL
142-82-5	n-Heptane	500	-		TWA (8 h)	WEL
	n-Heptane	-	-		STEL (15 min)	WEL

8.2 Exposure controls

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Treat subsequently with skin cream.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Hand protection

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01

**PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE**

00623-0001

Splash protection:

Protective gloves resistant to chemicals made off butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Eye wash bottle with pure water.

Tightly fitting goggles

Skin protection

Solvent-resistant apron.

9. Physical and chemical properties**9.1 General information**

Physical state : Liquid
 Colour : Colourless, Milky
 Odour : Hydrocarbon-like

9.2 Important health, safety and environmental information

		Test method
Changes in the physical state		
Boiling point :	> 56 °C	
Flash point :	- 20 °C	
Flammability		
Lower explosion limits :	1,1 vol. %	
Upper explosion limits :	13,2 vol. %	
Ignition temperature :	204 °C	
Vapour pressure :	233 hPa	Acetone
at (20 °C)		
Density (at 20 °C) :	0,72 g/cm ³	
Water solubility :	Partially miscible	
at (20 °C)		
Viscosity / dynamic :	5000 mPa·s	
Flow time :	> 30 s	3 DIN/ISO 2431
Solvent content		
89 - 91 %		

10. Stability and reactivity**Conditions to avoid**

To avoid thermal decomposition, do not overheat.
 Vapour/air mixtures are explosive at intensive warming.
 Heating can release vapours which can be ignited.

Materials to avoid

Strong oxidizing agents

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01



PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

00623-0001

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information

Empirical data on effects on humans

Vapours may cause drowsiness and dizziness.

Irritating to skin.

May cause irritation of the mucous membranes.

Effects of breathing high concentrations of vapour may include. Headache, dizziness, weakness, unconsciousness.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Contact with eyes may cause irritation.

Attention. Beware, danger of aspiration!

12. Ecological information

Additional information

Do not flush into surface water or sanitary sewer system.

Slightly water hazardous.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products :

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

14. Transport information

Land transport (ADR/RID)

ADR/RID class : 3
Hazard-no. : 33
UN number : 1133

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01

**PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE**00623-0001

Hazard label : 3
ADR/RID packing group : II

Description of the goods

Adhesives

Remarks (land transport)

LQ 6: combination packaging: 5 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Inland waterways transport**Marine transport**

IMDG code : 3
UN number : 1133
Marine pollutant : No
EmS : F-E; S-D
IMDG packing group : II
Hazard label : 3

Description of the goods

ADHESIVES

Remarks (marine transport)

Limited quantities (chapter 3.4): combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass)

Air transport

ICAO/IATA-DGR : 3
UN/ID number : 1133
Hazard label : 3
IATA-packing instructions - Passenger : 305
IATA-max. quantity - Passenger : 5 L
IATA-packing instructions - Cargo : 307
IATA-max. quantity - Cargo : 60 L
ICAO packing group : II

Description of the goodsADHESIVES

15. Regulatory information**15.1 Labelling**

Labelling according to EC-guidelines :

According to EC-regulations the product is to be labelled as follows:

R phrases :

11 Highly flammable.
38 Irritating to skin.
67 Vapours may cause drowsiness and dizziness.
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S phrases :

09 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
25 Avoid contact with eyes.

Safety Data Sheet according to 91/155/EEC

PREMA GmbH

Revision date : 26.10.2005

Revision no. : 1,01



PREMA ULTRA FAST DRYING VULKANIZING CEMENT, FLAMMABLE

00623-0001

-
- 29 Do not empty into drains.
 - 33 Take precautionary measures against static discharges.
 - 60 This material and its container must be disposed of as hazardous waste.
 - 61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

15.2 National regulations

Water contaminating class : 1 - slightly water contaminating
1999/13/EC (VOC) : 89 - 91 %

16. Other information

List of relevant R phrases

- 11 Highly flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 50 Very toxic to aquatic organisms.
- 53 May cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other data

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"
